C SERIES COMMENTERI CO

WITH THE **C** SERIES MOBILE MIXER



AUTOMATION

Electronic control panel and digital display of yardage and materials make for a quick-start operation.



ONE-BUTTON OPERATION

Push and pour easy for anyone to use.



ACCURATE Electronic mix designs for exact mixtures

every time.



CONTROL Quality, quantity, and schedule.



2nd Generation C Series With Enhanced Technology



C The concrete is good every day. We don't have any problems. The trucks are consistent.

– R.J. Daigle & Sons, Baton Rouge, LA



TECHNOLOGY	Electronic conrol panel features Auto- Washout™, Auto-Stow™, digital displays for mix design, and yardage poured.
EASE OF USE	Driver can set gate controls, push one button and pour. Mixer has accountability to itself through advanced technology and engineering.
ELIMINATE RISK	Pre-programmed mix designs take the need out of having concrete experts on staff. Information is stored electronically for each job and mix, continually improving productivity, profits, and to lower costs.
SAFETY	A no-slip work platform, high illumination LED lights, and a wireless remote lets the operator work safely through their shift.





SPECS, FEATURES, AND OPTIONS

SPECIFICATIONS	Carrying Capacity	Water Tank	Cement Bin	Production Rate*		
C60	8-10 cu yd (6.12-7.65 m ³)	510 gal (1930 L)	115-140 cu ft (3.26-3.96 m ³)	60 cu yd/hr (45.87 m³/hr)		
STANDARD FEATURES						
AP-Touch™		Cemen Tech's proprietary, advanced one-touch control system. Simply select the mix design you need and the system auto adjusts to the correct mix. Pre-load unlimited mix designs so you're always ready for any job.				
Auto-Stow™	Easy to lower and r	Easy to lower and raise chute. This additional safety measure means you're traveling with a safely secured chute.				
Auto-Washout™	Quickly wash out or	Quickly wash out on the job site to prevent material build up.				
-	gh & Low Flow Admix Tank Operator control is simplified with automated admix tanks to ensure the exact amount of admixture is used every time th Digital Flow Meters					
Two-Speed Cement I	Bin Adjustable cement of	lischarge allows an op	erator to easily switch between concr	rete mixers and flowable fill applications.		
Sand, Stone & Ceme Bin Vibrators	nt Ensure materials ar	e delivered at a consis	tent rate with pre-programmed, auto	-adjustble vibrators.		
Dual Auger Cement Metering	Take the guesswork	out of pouring with co	nsistent mix designs within +/- 1 per	cent every time.		
Pump Master Auger with IBS Bearing	•	A homogeneous mixing auger in the industry for higher discharge height than standard dual mix section augers with an internal bearing system pre-loaded with oil for extended life.				
Work Platform	Put safety first with	Put safety first with a large work platform to ensure cement is properly and safely loaded.				
360 ⁰ Swivel	Swivel chute makes	Swivel chute makes concrete finishing easier by changing the flow of concrete in any direction.				
OPTIONS	More options availa	ble — contact your Ce	men Tech sales representative for de	etails.		
Color System		Need color? No problem! A hopper provides the ability to introduce color pigments into concrete for multiple				
Wireless Remote	Operators can move	Operators can move about the job site while maintaining control of the mixer.				
2-Yard Extension	Want to carry more	Want to carry more yards per trip? Extend the aggregate bin by 2 cubic yards for maximum capacity.				
Ticket Printer	Generate a custom	Generate a custom batch ticket for your customer.				
Additional Admix Sy	stems Add another admix	Add another admix system for mix designs requiring more than two admixes per job.				
Electronic Tarp	Secure aggregates	Secure aggregates during transit with a high-quality, UV resistant black mesh tarp.				
Strobe Lights	Brighten up your wo	Brighten up your work sites and create awareness for traffic around you with bright amber strobe lights.				
Spray-In Bin Liner	Get extra protection	Get extra protection and seal the inside of the aggregate bin with a heavy duty polyurea protective coating.				
Automated Gates	Reduce operator en	Reduce operator error — aggregate gates self adjust to the required height based on selected mix design.				

*Measurements provided are approximations.

TO LEARN HOW TO CONTROL YOUR CONCRETE, CALL 800.247.2464 OR VISIT CEMENTECH.COM.